
THIRD-ORDER LEVELING SEA LEVEL DATUM OF 1929 37-083-14
CANNEL CITY QUADRANGLE
140 KENTUCKY
N3745-W8315/15
DIAGRAM NJ 17-7
JENKINS

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Final adjustment of 1953

Edition of 10/30/73

PR: LFB/ale



NGS (USC&GS) VERTICAL CONTROL DATA

A. Quadrangle 370831

INDEX OF PERMANENT MARKS

MARK (USGS)	PAGE NO.	MARK (NGS)	PAGE NO.
13 JDN 1949 1002 TT 1 TWC 1949 784 TT 6 TWC 1949 996 TT 7 TWC 1949 993 TT 8 TWC 1949 970	3 4 4 & 5	M 11 1928 887.173	3
TT 13 TWC 1949 1124 TT 14 TWC 1949 970 TT 15 TWC 1949 1064 TT 16 TWC 1949 914	5 5 5 6		

· ·	
CANNEL CITY QUADRANGLE 140 KENTUCKY J. D. Nikolaus Book AV 106	37-083-14 3
1949	
LINE 1.	Feet
By J. D. Nikolaus, 1949; Book AV 106	
"M 11 1928 887.173" (NGS)	886 .9 70
U.E., on E. side of rd.; about 130 ft E. of NE. corner of house; 90 ft NE. of small wooden bridge; in base on SW. side of power pole; rail spike	939.57
U.E., on E. side of rd.; in base on W. side of power pole; rail spike	979.29
U.E., on N. side of rd.; 65 ft NW. of NW. corner of frame house; 4 ft NW. of NW. corner of small wooden bridge; in large flat outcrop of rock; chiseled square	1016.30
U.E., on N. side of rd.; 75 ft N. and 12 ft E. of intersection of hwy. and Y-rd. NE.; on N. end of concrete culvert headwall; chiseled square	1048.40
Adele; 500 ft SE. of rd. junction; in NW. corner of Church of God church yard; 26 ft SW. of centerline of rd.; 13.2 ft W. of NW. corner of church; 2 ft E. of fenceline; in concrete post; standard tablet stamped "13 JDN 1949 1002"	1002.413
Reference mark; 60 ft N. of tablet; 3 ft NE. of fenceline; 20 ft NE. of corner fence post; in base on N. side of power pole; rail spike	1001.71
U.E., on N. side of rd.; at NW. end of small concrete drain- pipe at foot of stone steps leading to farmhouse; 180 ft W. of intersection of rd. and T-rd. N.; chiseled square	1043.26
<pre>U.E., on N. side of rd.; on crest of hill at E. end of deep cut; on large ledge outcrop; chiseled square</pre>	1083.24
LINE 2.	
By R. H. Paine, 1949; Book AV 112	
U.E., on curve; 15 ft E. of rd.; on E. end of tile culvert; chiseled square	726.26
U.E., at Y-rd. fork; 22 ft NE. of N. point of triangle; on E. end of tile culvert; chiseled square	728.15

4

LINE 2 (Cont'd.)

Feet

Scranton School, 0.25 mi E. to Y-rd., thence 0.1 mi S. along Y-rd.; 16 ft E. of centerline of rd.; set vertically in limestone bluff; standard tablet stamped "TT 1 TWC 1949 784" (Reported destroyed, 1975)

784.138

LINE 3.

By R. H. Paine, 1949; Book AV 112

U.E., Wellington, 1.2 mi SE. of post office, along U. S. Highway 460; on N. end of W. stone headwall of culvert; chiseled square

1089.54

Wellington, 1.5 mi SE. of post office, along U. S. Highway 460; 14 ft NE. of hwy.; 50 ft SE. of T-rd. fork; in top of N. end of NE. rail wall of concrete bridge over Broke Leg Creek; standard tablet stamped "TT 6 TWC 1949 996"

995.760

Reference mark; 40 ft SSE. of tablet; 80 ft SE. of T-rd. fork; 15 ft SSW. of U. S. Highway 460; on SW. end of SE. stone abutment of concrete bridge; chiseled square

992.56

U.E., Wellington, 1.5 mi SE. of post office, along U. S. Highway 460, thence about 300 ft SE. of T-rd. fork; on NE. side of rd.; in E. corner of wooden bridge; copper nail and washer

1007.61

U.E., Wellington, 1.5 mi SE. of post office, along U. S. Highway 460, thence 1.3 mi S. along rd.; on NW. side of rd.; 95 ft SW. of lane SE. to house; 23 ft NE. of lane NW. to house; in NW. side of wooden bridge; copper nail and washer

1037.11

U.E., Wellington, 1.5 mi SE. of post office, along U. S. Highway 460, thence 1.4 mi S. along rd.; on SW. side of rd.; on SW. stone headwall of culvert; chiseled square

1026.10

Wellington, 1.5 mi SE. of post office, along U. S. Highway 460, thence 1.9 mi SW. along Broke Leg Creek Road; 15 ft W. of centerline of rd.; 50 ft SE. of old store building; 2 ft E. of wire fence; in concrete post; standard tablet stamped "TT 7 TWC 1949 993" (Not found, 1975)

992.644

Reference mark; 78 ft N. of tablet; 13 ft W. of rd.; in root on E. side of 12-in. white oak tree; copper nail and washer

993.40

U.E., Wellington, 1.5 mi SE. of, along U. S. Highway 460, thence 2.2 mi SW. along rd.; 45 ft NE. of Y-rd. fork; on SE. side of rd.; on top of boulder; chiseled square

940.65

/Jogs into Frenchburg quadrangle/

ITME 3 (Cont.)	
LINE 3 (Cont'd.)	<u>Feet</u>
Stoll, 180 ft E. of post office; 95 ft SE. of Y-rd. fork; 18 ft E. of wooden bridge over small stream; 11 ft W. of 30-in. white oak tree; in concrete post; standard tablet stamped "TT 8 TWC 1949 970" (Reported not found, 1963)	970.129
Reference mark; 43 ft W. of tablet; 29 ft NW. of NW. corner of wooden bridge; 13 ft SW. of rd.; in root on W. side of double trunked 8-in. hickory tree; copper nail and washer	970.68
Valeria, 0.6 mi SE. of post office, along dirt rd. to cross trails, thence 0.3 mi SE. up mountain trail; 15 ft N. of centerline of rd.; 3.5 ft N. of barbed wire fence; on highest point on NW. end of ridge; in concrete post; standard tablet stamped "TT 13 TWC 1949 1124"	1123.560
Reference mark; 105 ft SSE. of tablet; 9 ft NE. of rd.; in fenceline; in root on W. side of 12-in. hickory tree; copper nail and washer	1118.87
U.E., Valeria, 2.4 mi SE. of post office; at steel girder bridge over Red River; at NE. end of NW. stone pier; on stone bridge seat; chiseled square	860.33
U.E., Gosneyville, 0.3 mi N. of post office, along rd.; at top of steep hill; at N. end of passable rd.; 6 ft W. of rd.; 40 ft E. of SE. corner of house; on boulder; chiseled square	958.99
Gosneyville; 30 ft NW. of gate entrance to post office; 15 ft W. of centerline of rd.; 8.5 ft NE. of gatepost; in concrete post; standard tablet stamped "TT 14 TWC 1949 970" (Reported not found, 1963)	969.612
Reference mark; 27 ft ESE. of tablet; 11 ft E. of rd.; on N. side of lane E. to Gosneyville Post Office; in base of N. gatepost; rail spike	966.52
Stillwater, 2.0 mi N. of post office, along abandoned logging rd.; 11 ft N. of centerline of rd.; 18 ft E. of triple white oak tree; 1 ft N. of wire fence; in concrete post; standard tablet stamped "TT 15 TWC 1949 1064"	1063.939
Reference mark; 17 ft WNW. of tablet; 14 ft N. of rd.; in base on E. side of 38-in. forked white oak tree; rail spike	1064.57

LINE 3 (Cont'd.)	<u>Feet</u>
U.E., Stillwater, 1.8 mi N. of post office, along abandoned logging rd.; 6 ft S. of trail; on W. end of 7- by 15-ft sandstone boulder; chiseled square	980.00
U.E., Stillwater, 1.0 mi N. of post office, along abandoned logging rd.; 7 ft NE. of trail; on rock outcrop; chiseled square	1012.95
U.E., Stillwater, 0.4 mi N. of post office, along abandoned logging rd.; at right-angle turn (rd. N. and E.); 12 ft NE. of traveled part of rd.; on rock ledge; chiseled square	1001.57
Stillwater, 260 ft W. of post office, along State Highway 15; in NE. end of concrete bridge over Stillwater Creek; standard tablet stamped "TT 16 TWC 1949 914"	913,808
Reference mark; 250 ft SW. of tablet; 45 ft SE. of State Highway 15; 112 ft SW. of SW. corner of concrete bridge; in NW. side of 12-in. apple tree; rail spike	918.67
U.E., Stillwater, 0.6 mi SW. of post office, along rd.; 13 ft NW. along State Highway 1812; on SW. end of NW. concrete headwall of culvert; chiseled square	919.64

HORIZONTAL CONTROL NORTH AMERICAN DATUM OF 1927

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

37-083-14
CANNEL CITY GUADRANGLE
140 KENTUCKY
N3745-W8315/15
DIAGRAM NJ 17-7
JENKINS

Elliott, Magoffin, Menifee, Morgan, and Wolfe Counties

Edition of 10/15/76

FRENCHBURG

(141)

PR: CRV/rmm

Plane coordinates are based on Lambert projection, Kentucky, North and South Zones

Only the permanent marks are listed for control classified obsolete and are not shown on sketch

MOREHEAD (163)

Cannel City

DINGUS (139)

LEE CITY (116) 372451

DISCLAIMER

We no longer attest to the validity of the positions listed for horizontal control established by transit traverse procedures. This control is now considered OBSOLETE and is included in this list for the purpose of identification only.

INDEX OF PERMANENT MARKS

MARK (USGS)	PAGE NO.
13 JDN 1949 1002 IT 1 TWC 1949 784 IT 6 TWC 1949 996 IT 7 TWC 1949 993 IT 8 TWC 1949 970 IT 11 TWC 1949 IT 12 TWC 1949 IT 13 TWC 1949 IT 14 TWC 1949 1124 IT 14 TWC 1949 970 IT 15 TWC 1949 1064 IT 16 TWC 1949 914	5 3 3 3 5 5 3 3 3 3 3 3 3 3 3 3 3 3 3 3
NGS	
K 11 1928 813.637 L 11 1928 840.648 M 11 1928 887.173 J 90 1935 845.264 L 90 1935 768.135 N 90 1935 929.923 Q 90 1935 1021.960 S 90 1935 777.827	4 5 5 4 4 4

STATION DESCRIPTION PLANE COORDINATES, FEET

LATITUDE 0 1 11

LONGITUDE

The following positions are considered OBSOLETE. To be used only to locate permanent marks in the field.

By T. W. Cayce, 1949: Book AH 142

Scranton School, 0.25 mi E. to Y-rd., thence 0.1 mi S. along Y-rd.; 16 ft E. of centerline of rd.; set vertically in limestone bluff; standard tablet stamped "IT 1 TWC 1949 784" (Reported destroyed, 1975)

Ky. N.) X = 2.217.164 Y = 180.390

37 59 34.54

83 29 47.28

Wellington, 1.5 mi SE. of post office, along U. S. Highway; 460; 14 ft NE. of centerline of hwy.; 50 ft SE. of junction of I-rd. SW.; in N. end of NE. rail wall of concrete bridge over Broke Leg Creek; standard tablet stamped "TT 6 TWC 1949 996"

X = 2,218,531 Y = 148,806

37 54 22,20

83 29 33,45

Wellington, 1.5 mi SE. of post office, along U. S. Highway 460, thence 1.9 mi SW. along Broke Leg Creek Road; 15 ft W. of centerline of rd.; 50 ft SE. of old store building; 2 ft E. of wire fence; in concrete post; standard tablet stamped "TT 7 TWC 1949 993" (Not found, 1975)

X = 2.217.280

Y = 140.403

37 52 59.24

83 29 49.92

Stoll, 180 ft E. of post office; 95 ft SE. of junction of Y-rd.; 18 ft E. of center of wooden bridge over small stream; 11 ft W. of 30-in. white oak tree; in concrete post; standard tablet stamped "TT 8 TWC 1949 970" (Not found, 1963)

X = 2.217.273 Y = 132.842

37 51 44.49

83 29 50.78

Valeria, 0.6 mi SE. of post office, along dirt rd. to cross trail, thence 0.3 mi SE. up mountain trail; 15 ft N. of centerline of rd.; 3.5 ft N. of barbed wire fence; on highest point of NW. end of ridge; in concrete post; standard tablet stamped "TT 13 TWC 1949 1124"

X = 2.216.876

Y = 116.231

37 49 00.31

83 29 57.40

Gosneyville; 30 ft NW. of gate entrance to post office; 15 ft W. of centerline of rd.; 8.5 ft NE. of gatepost; in concrete post; standard tablet stamped "TI 14 TWC 1949 970" (Not found, 1963)

X = 2.220.306

Y = 107.875

37 47 37.43

83 29 15.54

Stillwater, 2.0 mi N. of post office, along abandoned logging rd.; ll ft N. of centerline of rd.; l8 ft E. of triple white oak tree; 1 ft N. of wire fence; in concrete post; standard tablet stamped "IT 15 TWC 1949 1064"

X = 2.219.427

Y = 100.451

37 46 24.11

83 29 27-24

Stillwater; 260 ft W. of post office, along State Highway 15; in NE. end of concrete birdge over Stillwater Creek; standard tablet stamped "TT 16 TWC 1949 914"

X = 2,220,771

Y = 94.418

37 45 24.34

83 29 11.12

STATION

DESCRIPTION PLANE COORDINATES, FEET

LATITUDE 0 1 11 LONGITUDE

OBSOLETE MARKS (Cont'd.)

Wrigley, 2.2 mi S. of post office, along State Highway 7; 14 ft N. of centerline of hwy.; 145 ft S. of log house; 12 ft W. of drive to house; in E. end of N. concrete headwall of culvert; NGS standard disk stamped "J 90 1935 845.264"

Ky. N.)

X = 2.280.856

Y = 180.363

37 59 28,37

83 16 31.72

West Liberty, 4.4 mi NW. of courthouse along State Highway 7; 60 ft SE. of centerline of hwy. at junction of rd. SE.; 14 ft E. of centerline of rd.; in N. end of E. concrete headwall of culvert over small stream; standard tablet stamped "TT 11 TWC 1949"

X = 2.279.276

Y = 170.274

37 57 48.80

83 16 52.79

West Liberty, 2.7 mi NW. of courthouse, along State Highway 7; at concrete bridge over Elk Fork; 12 ft S. of centerline of hwy.; in S. end of E. abutment; NGS standard disk stamped "L 90 1935 768.135"

X = 2.278.891 Y = 162.659

37 56 33.59

83 16 58.62

West Liberty; at W. entrance to county courthouse; 6 ft S. of S. end of steps; 49 ft E. of centerline of Main Street; set vertically in steps; NGS standard disk stamped "N 90 1935 929.923"

X = 2.285.564 Y = 154.609

37 55 13.28

83 15 36.38

West Liberty, 1.4 mi S. of courthouse, along U. S. Highway 460; 29 ft E. of, and 1 ft higher than centerline of hwy.; 8 ft W. of fenceline; in concrete post; NGS standard disk stamped "Q 90 1935 1021.960"

X = 2.282.759 Y = 149.885

37 54 26.88

83 16 12.01

Index: 28 ft E. of centerline of U. S. Highway 460 at junction of State Highway 191; 36 ft N. of NW. corner of store: 4 ft W. of board fence; in concrete post; NGS standard disk stamped "S 90 1935 777.827"

X = 2.278.504 Y = 146.389

37 53 52.79

83 17 05.55

Malone: 310 ft NW. of post office, along State Highway 191; 12 ft SW. of centerline of hwy.; in NW. end of SW. concrete headwall of culvert over drain; standard tablet stamped "TT 12 TWC 1949"

X = 2.286.224 Y = 137.048

37 52 19.62

83 15 30.50

Malone, 1.8 mi S. of, along State Highway 191; 10 ft E. of centerline of hwy.; in S. end of E. concrete headwall of culvert; NGS standard disk stamped "K 11 1928 813.637"

X = 2.286.115

Y = 129.701

37 51 07.00

83 15 32.85

STATION

DN DESCRIPTION
PLANE COORDINATES, FEET

LAT ITUDE

LONGITUDE

OBSOLETE MARKS (Cont'd.)

Cannel City, 2.5 mi NE. of, along State Highway 191; in SW. end of bridge over Caney Creek; NGS standard disk stamped "L 11 1928 840.648"

X = 2,287,204

Y = 118,318

37 49 14,36

83 15 20.79

Cannel City; at old site of Morgan County National Bank; at NE. corner of old foundation; in W. end of fourth step; NGS standard disk stamped "M 11 1928 887.173"

X = 2.282.385

Y = 106.865

37 47 21.66

83 16 22.36

Adele; 500 ft SE. of rd. junction; in NW. corner of Church of God church yard; 26 ft SW. of centerline of rd.; 13.2 ft W. of NW. corner of church; 2 ft E. of fenceline; in concrete post; standard tablet stamped "13 JDN 1949 1002" (Reported destroyed, 1965)

X = 2,274,572

Y = 94,606

37 45 21.27

83 18 01.25